



GK-3[®]

Technical Specifications



Motor -	1/17 horsepower
Output Speed -	20-60 cycles per second (LOW, MED, HIGH)
Power Source -	110v or 220v (other voltages available)
Speed Control -	Solid State Electronic
Current Leakage -	under 75 MicroAmps
Power Cord -	10' hospital grade
Drive Cable -	5'
Housing Material -	ABS Cicolac
Configurations -	Caster-stand mounted or table-top mounted
Unit Dimensions -	10" H x 4" W x 4" D
Assembled Dimensions -	44" H x 21" W x 21" D
Unit Weight -	13.5 Lbs.
Assembled Unit Weight -	23 Lbs.
Shipping Dimensions -	22" x 21" x 17 ^{3/8} "
Shipping Weight -	33 Lbs. (varies based on applicator package)
Applicator Packages -	PRO-PKG or RT-PKG recommended
Timer -	No
Applicator Storage -	Yes - tray



GENERAL PHYSIOTHERAPY, INC.
13222 LAKEFRONT DRIVE - EARTH CITY (ST. LOUIS), MISSOURI 63045-1504 - USA
PHONE: (314) 291-1442 TOLL FREE: (800) 237-1832 FAX: (314) 291-1485
www.g5.com



The Symbol of Quality
and Reliability in
Massage Machines™